



Olympia Micro *ClimaPlus*[™]

Fine textured panel



Features and Benefits

- Economical, fine-textured panel.
- Excellent light reflectance enhances indirect lighting of a space.
- *CLIMAPLUS*[™] 15-year Lifetime System Warranty to withstand conditions up to 104 °F (40 °C)/90% relative humidity without visible sag when used with USG's *DONN*[®] Brand Suspension Systems.

Applications

- Classrooms
- Hotels
- Reception and lobby areas
- Restaurants
- Retail stores

Olympia Micro Panels with *CLIMAPLUS*[™] Performance/*DONN*[®] Brand *FINELINE*[®] Suspension System






Olympia Micro ClimaPlus™

Acoustical Ceilings

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC2180




UL Classified








Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Panel Cost
Olympia Micro CLIMAPlus™ Panels 	2' x2' x5/8"	Class A	4211	.50	30	.85	White	A, B, C	52%	\$\$
	2' x4' x5/8"	Class A	4411	.50	30	.85	White	A, B	52%	\$\$
(SLT) 	2' x2' x5/8"	Class A	4221	.50	35	.85	White	D	52%	\$\$
	2' x4' x5/8"	Class A	4421	.50	35	.85	White	D	52%	\$\$
(FLB) 	2' x2' x5/8"	Class A	4231	.50	35	.85	White	E, F, G	52%	\$\$
	2' x4' x5/8"	Class A	4431	.50	35	.85	White	E, F, G	52%	\$\$
Olympia Micro CLIMAPlus™ Illusion Two/24 Panels The look of 2' x 2' panels 	2' x4' x3/4"	Class A	4742	.50	35	.85	White	D	52%	\$\$
	(ILT) 	2' x2' x3/4"	Class A	4744	.50	35	.85	White	E	52%

Illusion Two/24

Patterns



Grid Profile Options

A DONN® DX®/ DXL™	B DONN DXW™	C CENTRICITEE™	D DONN DX/DXL	E CENTRICITEE	F FINELINE 1/8®	G FINELINE
						

ASTM E1264 classification
Type III, Form 2, Pattern CE
ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 10

Weight
0.92 lb./ft.²
Thermal resistance
R-1.4 (5/8" panels)
R-1.7 (3/4" panels)
Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Footnotes
1. LR values are shown as averages.
2. For details, see the Recycled Content selector.
3. Panels have 15/16" routing.

SAFETY FIRST!
Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company:
CENTRICITEE, CLIMAPlus, DONN, DX, DXL, DXW, FINELINE, USG.

SC2180/6-04
© 2004, USG Interiors, Inc.
Printed in U.S.A.