



Millennia[®] *ClimaPlus*[™]



Smooth textured panel

Features and Benefits

- Market's fastest-installing smooth ceiling is an economical alternative to face-laminated panels.
- NRC meets general office acoustical needs for sound absorption.
- *CLIMAPLUS*[™] 30-year Lifetime System Warranty to withstand conditions up to 104 °F (40 °C)/ 95% relative humidity without visible sag when used with USG's *DONN*[®] Brand Suspension Systems.
- Panel used in *RENDITIONS*[™] Face-Routed Ceiling Systems (see IC327).

Applications

- Retail stores
- Hospitality
- Office and conference areas
- Party rooms
- Reception and lobby areas
- Transportation terminals

Millennia® ClimaPlus™

Acoustical Ceilings

Technical Service 800.USG.4YOU
Web Site www.usg.com
Samples/Literature 888.874.2450
Samples/Literature Fax 888.874.2348
Customer Service 800.950.3839
Literature Number SC1824



UL Classified

	Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Panel Cost
MILLENNIA® CLIMAPLUS™ Panels	(SQ)	2' x2' x3/4"	Class A	76505	.70	35	.85	White	A, B, C	72%	\$\$
		2' x4' x3/4"	Class A	78505	.70	35	.85	White	A, B	72%	\$\$
	(SLT)	2' x2' x3/4"	Class A	76705	.70	35	.85	White	D	72%	\$\$
		2' x4' x3/4"	Class A	78705	.70	35	.85	White	D	72%	\$\$
	(FLB)	2' x2' x3/4"	Class A	76907	.70	35	.85	White	E, F, G	72%	\$\$
		2' x4' x3/4"	Class A	76901	.70	35	.85	White	E, F, G	72%	\$\$
MILLENNIA CLIMAPLUS Tile ³	(BESK)	12" x12" x3/4"	Class A	70003	.60	40	.85	White	H	72%	\$\$\$\$
MILLENNIA CLIMAPLUS Illusion Two/24 Panels The look of 2'x2' panels	(SLT) ⁴	2' x4' x3/4"	Class A	78780	.70	35	.85	White	D	72%	\$\$
	 (ILT) ⁵	2' x4' x3/4"	Class A	78080	.70	35	.85	White	I	72%	\$\$

Patterns	Illusion Two/24	RENDITIONS™⁶

	A	B	C	D	E	F	G	H	I
Grid Profile Options	DONN® DX®/ DXL™	DONN DXW™	CENTRICITEE™	DONN DX/DXL	CENTRICITEE	FINELINE® 1/8	FINELINE	DONN DX/DXL Concealed	CENTRICITEE

ASTM E1264 classification
Type III, Form 1 or 2, Pattern G
ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 25
Weight
1.04 lb./ft.² (panels and tile)

Thermal resistance
R-2.6
Maximum backloading
See Warranty for details.
Maintenance
Can be cleaned easily with a soft brush or vacuum.

Patented technology
This product's unique combination of sag resistance and sound performance results from a technology covered by U.S. Patent No. 5,250,153.
Footnotes
1. LR values are shown as averages.
2. For details, see the Recycled Content selector.

3. Contact USG for adhesive recommendations for 12" x12" glue-up applications.
4. Panels have a 15/16" routing.
5. Panels have a 9/16" routing.
6. See RENDITIONS Face-Routed Ceiling Panels (IC327) in USG Specialty Ceilings binder for more information.

SAFETY FIRST!
Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company: CENTRICITEE, CLIMAPLUS, DONN, DX, DXW, FINELINE, FIRECODE, MILLENNIA, RENDITIONS, USG.

SC1824/rev. 6-04
© 2004, USG Interiors, Inc.
Printed in U.S.A.