


















Features and Benefits

- Non-directional pattern with a fresh, clean appearance offers fast, efficient installation.
- Economical, all-purpose ceiling pattern offered in many sizes.
- Available in several standard colors for design flexibility.
- Optional FIRECODE™ formulation designed to meet life safety codes.

Applications

- Schools
- Corridors
- Offices
- Retail stores

	Panel Size		Item No.  UL Classified				Color ⁴	Grid Options	Recycled Content ⁶	Panel Cost	
	Edge	Imperial Metric (mm) ¹	Class ²	Imperial Metric	NRC	CAC Min.					LR ³
RADAR TM Panels	(SQ) 	2' x2' x5/8"	Class A	2110	.55	33	.84	White	A, B, C	25%	\$
		600x600x15		ME2110							
		2' x2' x5/8"		2115	.55	35	.84	White	A	46%	\$
		2' x4' x5/8"	Class A	2310	.55	35	.84	White	A, B	25%	\$
		600x1200x15		ME2310							
		2' x4' x5/8"		2315	.55	35	.84	White	A	46%	\$
		2' x4' x5/8"	Class A	2310P ⁵	.55	35	.84	White	A, B	25%	\$
		2' x5' x5/8"	Class A	2619	.55	35	.84	White	A, B	25%	\$
		20" x60" x5/8"	Class A	2617	.55	35	.84	White	A, B	25%	\$
	2' x4' x3/4"	Class A	2311	.60	35	.84	White	A, B	25%	\$	
	30" x60" x3/4"	Class A	2618	.60	35	.84	White	A, B	25%	\$	
	(SLT) 	2' x2' x5/8"	Class A	2120	.55	33	.84	White	D	25%	\$
		600x600x15		ME2120							
2' x2' x5/8"			2125	.55	35	.84	White	D	46%	\$	
2' x4' x5/8"		Class A	2320	.55	35	.84	White	D	25%	\$	
(FLB) 	2' x2' x5/8"	Class A	2130	.55	33	.84	White	E, F, G	25%	\$	
RADAR Tile ⁶	(BESK) 	12" x12" x5/8"	Class A	2990	.50	40	.84	White	H	25%	\$\$\$
											
	A DONN [®] DX [®] / DXL [™]	B DONN DXW [™]	C CENTRICTEE [™]	D DONN DX/DXL	E CENTRICTEE ⁷	F FINELINE [®] 1/8	G FINELINE	H DONN DX/DXL Concealed			
Grid Profile Options											

ASTM E1264 classification
 Type III, Form 2, Pattern CD
ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 10

Imperial weight
 .69-.81 lb./ft.² (Class A 5/8" panels)
 1.00 lb./ft.² (Class A 3/4" panels)
 1.10 lb./ft.² (Class A 5/8" tile)
 1.15 lb./ft.² (FIRECODE[™] panels)
Metric weight
 3.37-3.95 kg/m² (Class A 15 mm panels)

Thermal resistance
 R-1.5 (Class A, 5/8" panels and tile)
 R-1.7 (Class A, 3/4" panels)
 R-1.4 (Class A, 15 mm panels)
 R-1.6 (FIRECODE, 5/8" panels)
Maximum backloading
 See Warranty for details.
Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Footnotes
 1. Metric available in White only.
 2. Fire-rated items: see UL design details.
 3. LR values are shown as averages.
 4. See color selectors for more information.
 5. Includes plastic coating, Gardner-Scrubability-tested to 3,000 cycles (ASTM D246).
 6. Contact USG for adhesive recommendation for 12" x 12" glue-up applications.
 7. Maximum 2' x 2' for square panels.

SAFETY FIRST!
 Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.