



Sandrif[™] ClimaPlus[™]

Medium textured panel



Features and Benefits

- Uniquely textured cast product with durable surface that resists scrapes commonly caused by accessing the ceiling plenum.
- Integral color masks nicks and scratches and enhances lifelong panel appearance.
- Extensive color selection provides multiple design options.
- Optional FIRECODE[™] formulation designed to meet life safety codes.
- CLIMAPLUS[™] 15-year System Warranty to withstand conditions up to 104 °F (40 °C)/90% relative humidity without visible sag when used with USG's DONN[®] Brand Suspension Systems.

Applications








- Conference and lobby areas
- Department stores
- Entertainment and gaming
- Executive offices
- Hotels
- Media centers
- Restaurants

Sandrifit™ ClimaPlus™

Acoustical Ceilings

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC1841

UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color ²	Grid Options	Recycled Content ³	Panel Cost
SANDRIFT™ CLIMAPLUS™ Panels	(SL) 	Class A	808	.70 	38 	.83	White Advantage	A	67%	\$\$\$
	(FL) 	Class A	809	.70 	38 	.83	White Advantage	B, C, D	67%	\$\$\$
Grid Profile Options		A DONN® DX®/ DXL™	B CENTRICITEE™	C FINELINE® 1/8	D FINELINE					
										

FIRECODE™ formulation

2'x2'x3/4" SL-edge panel with FIRECODE formulation is available without CLIMAPLUS performance (Item No. 815).

ASTM E1264 classification

Type III, Form 4, Pattern Z

ASTM E84 surface burning characteristics

Class A
Flame spread: 25
Smoke developed: 15

Weight

1.55 lb./ft.² (Class A)
1.60 lb./ft.² (FIRECODE)

Thermal resistance

R-1.6 (Class A)
R-1.1 (FIRECODE)

Maximum backloading

See Warranty for details.

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Texture

The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production date code.

Footnotes

1. LR values are shown as averages.
2. To highlight the unique texture of SANDRIFT CLIMAPLUS panels, choose light colors. See color selectors for more information.
3. For details, see the Recycled Content selector.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company:
CENTRICITEE, CLIMAPLUS, DONN, DX, DXL, FINELINE, FIRECODE, SANDRIFT, USG.

SC1841/rev. 6-04
© 2004, USG Interiors, Inc.
Printed in U.S.A.